



SIDER

OXYHARD

OXYDRO



Description

OxyHard is a multi-surface liquid hardener.

Use

OxyHard is suitable to use on concrete, limestone, fiber-cement or traditional mortar whether it is old or new. OxyHard chemically hardens the concrete surface while curing. OxyHard is also well suited for use on recently cured or older floor surfaces; providing added abrasion resistance and mechanical properties.

Specifications

Density	1.10
Dry Extract	11%
Ph	<2

Surface Preparation

Surface must be cured, clean and free of bond inhibiting particles, however, OxyHard may be applied directly to a dry or damp surface.

Application Procedures

OxyHard is ready to use. Apply 2 coats evenly with a brush or a hand sprayer. Allow 6 hours of drying time between each coat. Final hardness is achieved after 4 days. Lightly rinse the surface with water once fully dried.

Coverage

250 f² (23.23 m²) per 1 gallon (3.8 liters).

Packaging

1 gallon (3.8 liters) container.

Storage and Shelf Life

Shelter in a dry environment from direct sunlight, extreme heat, rain and freezing. Shelf life is one year in original sealed packaging.

Sider-Oxydro products are specifically formulated and designed to meet and exceed industry standards. Please refer to technical data sheets for specific installation instructions or contact Sider-Oxydro for application questions.