



SIDER

**OXYMOSS CLEANER
OXYMOSS SEALANT**

OXYDRO



Description

OxyMoss Cleaner is a ready-to-use, clear preventive and cleaning treatment against mildew and moss growth on concrete surfaces, tile, brick and stone. After the OxyMoss Cleaner treatment is applied to these surfaces, the clear OxyMoss Sealant is applied to lengthen the protection for these surfaces.

Use

OxyMoss Cleaner is used to clean and prevent mildew or moss growth on all types of surfaces exposed to constant humid conditions such as tennis courts, stucco, stone or brick surfaces and all concrete surfaces. OxyMoss Sealant is a clear and durable sealant that serves to lengthen the protection of these cleaned surfaces.

Application Procedure

Cleaning

Spray the surface to be treated using a hand sprayer at a ratio of 1 quart (1 liter) of OxyMoss Cleaner for a surface area of 40 to 50 f² feet (4 to 5 m²) and allow one week to set. Then, pressure-wash the surface or manually wash down the surface with a brush and water hose. Then follow preventive treatment procedures.

Preventive Treatment

Spray the surface to be treated using a hand sprayer at a ratio of 1 quart (1liter) of OxyMoss Cleaner for a surface area of 50 to 80 f² (5 to 8 m²). Do not rinse. OxyMoss Cleaner will re-activate on its own during humid conditions. Treat only once a year.

After surfaces have dried, apply a thin, sprayed layer of OxyMoss Sealant to the surface and allow to dry. OxyMoss Sealant will extend the benefits of the preventative treatment.

Treat the surface during dry ambient conditions. Avoid treatment before or after rain. Avoid treatment during freezing temperatures or if temperatures exceed 90° F (32° C). Treat preferably during fall or spring season.



SIDER

**OXYMOSS CLEANER
OXYMOSS SEALANT**

OXYDRO

**Safety
Recommendations**

It is strongly recommended to wear rubber gloves and protective goggles during application of OxyMoss Cleaner. In case of contact with skin or eyes, rinse thoroughly with water. See manufacturer's Material Safety Data Sheet for additional information.

Packaging

5 gallons (18.9 liters) pail.
1 gallon (3.8 liters) containers comprised of 4 each 1 gallon containers.

Coverage

800 to 1500 f² (80 to 150 m²) per 20 gallons (18.9 liters) pail.
150 to 300 f² (15 to 30 m²) per 1 gallon (3.8 liters) container.

Storage and Shelf Life

Shelter in a dry environment from direct sunlight, extreme heat, rain and freezing. Shelf life is one year in original sealed packaging.

Sider-Oxydro products are specifically formulated and designed to meet and exceed industry standards. Please refer to technical data sheets for specific installation instructions or contact Sider-Oxydro for application questions.