

**SIDER****SIDERFACADE****OXYDRO****Description**

SiderFacade is a clear, heavy-duty, non-siliconized liquid which bonds with the porous surfaces being treated to give a deep, penetrating protection against chloride induced corrosion or reinforcing steel and surface deterioration.

Use

SiderFacade is formulated to deeply penetrate the pores and capillaries of old or recently cured concrete (1 month minimum) or stone and brick surfaces with a thin, invisible coating, producing an extremely water repellent surface - even in the presence of small cracks in the surface to be treated. It is suitable for use on interior or exterior horizontal or vertical surfaces.

SiderSeal provides protection against:

- ↪ De-icing salts
- ↪ Moisture
- ↪ Weathering
- ↪ Freeze induced scaling

SiderSeal is ideally suited to protect roads, sidewalks, parking decks, parking ramps, wall and bridges exposed to weathering.

Specifications

Density .82
Flash Point 141° F (60° C)

Surface Preparation

Surfaces must be clean, cured, dust-free and free of release agents or contamination. Remove all paint, loose or damaged materials and rubber marks from the surface.

Limitations

Do not apply to dry or frozen surfaces. Protect from rain, freezing and thawing surfaces. Apply when ambient temperatures are above 41° F (5° C) and below 90° F (32° C). For application outside of these temperature ranges, please contact Sider-Oxydro, Inc. technical support for additional information.

Application Procedure

Flood horizontal surfaces using a low-pressure spray, roller or brush. Pour SiderFacade on the surface and sweep material around with a broom for complete and even coverage. Allow SiderFacade to penetrate the surface and apply a second coat before the first coat dries.

Vertical surfaces should receive a minimum of two coats applied with a low-pressure sprayer, standard paint brush or paint roller.

Provide adequate ventilation of area to be treated and use protective goggles and rubber gloves during application.

Packaging

5 gallons (20 liters) pail.

Coverage

.3 quarts (.3 liters) per 10.76 f² (1 m²).

Storage and Shelf Life

Shelter in a dry environment from direct sunlight, extreme heat, rain and freezing. Shelf life is one year in original sealed packaging.

Sider-Oxydro products are specifically formulated and designed to meet and exceed industry standards. Please refer to technical data sheets for specific installation instructions or contact Sider-Oxydro for application questions.