

**SIDER****SIDERFACADE****OXYDRO****Description**

SiderFacade is a clear, heavy-duty, non-siliconized liquid which bonds with the porous surfaces being treated to give a deep, penetrating protection against chloride induced corrosion or reinforcing steel and surface deterioration.

**Use**

SiderFacade is formulated to deeply penetrate the pores and capillaries of old or recently cured concrete (1 month minimum) or stone and brick surfaces with a thin, invisible coating, producing an extremely water repellent surface - even in the presence of small cracks in the surface to be treated. It is suitable for use on interior or exterior horizontal or vertical surfaces.

SiderSeal provides protection against:

- ↪ De-icing salts
- ↪ Moisture
- ↪ Weathering
- ↪ Freeze induced scaling

SiderSeal is ideally suited to protect roads, sidewalks, parking decks, parking ramps, wall and bridges exposed to weathering.

**Specifications**

Density .82  
Flash Point 141° F (60° C)

**Surface Preparation**

Surfaces must be clean, cured, dust-free and free of release agents or contamination. Remove all paint, loose or damaged materials and rubber marks from the surface.

**Limitations**

Do not apply to dry or frozen surfaces. Protect from rain, freezing and thawing surfaces. Apply when ambient temperatures are above 41° F (5° C) and below 90° F (32° C). For application outside of these temperature ranges, please contact Sider-Oxydro, Inc. technical support for additional information.

**Application Procedure**

Flood horizontal surfaces using a low-pressure spray, roller or brush. Pour SiderFacade on the surface and sweep material around with a broom for complete and even coverage. Allow SiderFacade to penetrate the surface and apply a second coat before the first coat dries.

Vertical surfaces should receive a minimum of two coats applied with a low-pressure sprayer, standard paint brush or paint roller.

Provide adequate ventilation of area to be treated and use protective goggles and rubber gloves during application.

**Packaging**

5 gallons (20 liters) pail.

**Coverage**

.3 quarts (.3 liters) per 10.76 f<sup>2</sup> (1 m<sup>2</sup>).

**Storage and Shelf Life**

Shelter in a dry environment from direct sunlight, extreme heat, rain and freezing. Shelf life is one year in original sealed packaging.

*Sider-Oxydro products are specifically formulated and designed to meet and exceed industry standards. Please refer to technical data sheets for specific installation instructions or contact Sider-Oxydro for application questions.*