

**SIDER****SIDERLASTIC****OXYDRO****Description**

SiderLastic is a flexible, polyurethane waterproofing membrane.

Use

SiderLastic is ideally suited for use on concrete balconies, concrete parking lots, buried structures or aerial structures. SiderLastic forms a protective barrier against severe weather and pollutants.

Specifications

Density	1.25
Adherence to concrete	435 psi - 3 MPa
Stretching capacity	150%
Crack tolerance	1.1 mm

Surface Preparation

Surface must be clean, dry and sound. Round off by mechanical means all sharp angles and fill all inside corners with SiderStructure reinforced with polyester mesh.

Mixing Instructions and Application Procedures

SiderLastic is ready to apply. Prime the surface with a coat of SiderLastic with a ratio of 90% to 95% SiderLastic and 5% to 10% of SiderUniversal Agent. Apply two coats of non-diluted SiderLastic with a standard paint roller or paint brush. Allow 6 to 24 hours between applications of each coat.

Coverage

30 f² (3 m²) per kit.

Packaging

3.5 lb. (1.6 kg) kit.

Storage and Shelf Life

Shelter in a dry environment from direct sunlight, extreme heat, rain and freezing. Shelf life is one year in original sealed packaging.

Sider-Oxydro products are specifically formulated and designed to meet and exceed industry standards. Please refer to technical data sheets for specific installation instructions or contact Sider-Oxydro for application questions.