

**SIDER****SIDERRESIN-M50****OXYDRO****Description**

SiderResin-M50 is an exceptional bonding agent for floor applications. The unique plasticizing properties of SiderResin-M50 allow for maximum stabilization of the concrete floor surface and serves as the perfect bonding medium.

Use

SiderResin-M50 is designed as the bonding agent when resurfacing floors with such products as SiderLevel, SiderFloor 2000, SiderFloor 4000, SiderFloor-SL Underlayment, SiderFloor Finish-HCR and other Sider-Oxydro concrete bonding and repair products for both interior and exterior applications.

Specifications

Liquid White

Limitations

Clean and prepare all surfaces by removing loose particles, dust, friable particles or any bond inhibiting agents such as asphalt or grease with a dry brush. Apply when ambient temperature is above 41° F (5° C) and below 86° F (30° C). Do not apply over heated or frozen surfaces

Mixing Instruction and Application Procedures

Mix SiderResin-M50 according to packaging instructions. To ensure maximum performance, always apply floor coating or concrete bonding and repair products a minimum of 30 minutes after the SiderResin-M50 has been applied to floor surface and no longer than 6 hours after application, according to the floor coating or concrete bonding and repair product directions for use.

Packaging

4 each - 5 quart (5 liter) carton.
1 each - 5 gallon (20 liter) pail.

Storage and Shelf Life

Shelter in a dry environment from direct sunlight, extreme heat, rain and freezing. Shelf life is one year in original sealed packaging.

Sider-Oxydro products are specifically formulated and designed to meet and exceed industry standards. Please refer to technical data sheets for specific installation instructions or contact Sider-Oxydro for application questions.