

**SIDER****SIDERSTOP****OXYDRO****Description**

SiderStop is a quick set hydraulic binder and is used for all types of concrete and masonry surfaces.

Use

SiderStop is designed to stop water leaks originating from cracks or holes in a walls or ceilings prior to applying a waterproofing or water repellent treatment. SiderStop is prepared in small quantities and used as needed to stop active water leaks or any type of water infiltration.

Specifications

Initial cure 1 minute at 85° F (20° C)
Final cure 5 minutes at 85° F (20° C)
Density 2

Surface Preparation

Surface must be clean and loose or damaged materials must be removed. Clean the surrounding and the inside of the hole or the crack and scrape off all excess materials. Enlarge the area to be repaired if necessary.

Limitations

Do not apply to dry or frozen surfaces. Protect from rain, freezing and thawing surfaces. Apply when ambient temperatures are above 41° F (5° C) and below 90° F (32° C). For application outside of these temperature ranges, please contact Sider-Oxydro, Inc. technical support for additional information.

Safety Precautions

Apply SiderStop while wearing rubber gloves.

Mixing Instruction and Application Procedures

Mix one part of clean potable water to 4 parts of SiderStop and mix by hand or using a drill and paddle. Apply as soon as possible directly to the area to be sealed. In case of running water, for SiderStop mud into the shape of a ball with your hands and apply as soon as possible to the area to be sealed. Hold the mud in place for 3 minutes by pressing with your hands. Then waterproof the entire surface area with a waterproofing or water repellent agent.

Acceptable waterproofing agents include:

- ↵ SiderSeal
- ↵ SiderProof (all formulas)
- ↵ SiderLastic
- ↵ SiderPool
- ↵ SiderRoof

Packaging

1 carton contains 4 - 11 lb. (5 kg) containers.
1 pail contains 55 lb. (25 kg).

Storage and Shelf Life

Shelter in a dry environment from direct sunlight, extreme heat, rain and freezing. Shelf life is six months in original sealed packaging.

Sider-Oxydro products are specifically formulated and designed to meet and exceed industry standards. Please refer to technical data sheets for specific installation instructions or contact Sider-Oxydro for application questions.

