

Total Quality. Total Service. Total Satisfaction.

T-WALL Glaze 2000

Description

T-WALL GLAZE 2000 is a high solids 100% acrylic emulsion, which is used as a protective clear coat over a variety of surfaces including masonry, EIFS and wood.

T-WALL GLAZE 2000 can produce either a satin finish or rich glossy finish on surfaces depending on the number of coats applied and application technique used.

T-WALL GLAZE 2000 is designed for exterior wall surfaces and will remain clear even when exposed to direct sunlight.

Application

Prepare surface by removing any dirt, oils, loose debris or any substance that may interfere with the bond. Allow the surface to dry. Previously sealed or treated surfaces should have a 4' by 4' test area coated with **T-WALL GLAZE 2000** to test adhesion. It is advisable to fill any spalled or broken areas of substrate with a suitable patching material prior to application of the coating. Any cracks should be filled with a paintable grade acrylic caulk and allow to cure 4 hours before beginning coating.

Stir product for 30 seconds with a low speed mixer or manually stick-stir as desired. Do not beat excessive air into the product. Apply by roller, brush or airless sprayer. When using a roller, the nap thickness can be varied to compensate for the substrate characteristics and the desired result.

Thin product with up to 5 ounces of water per gallon if needed. For higher sheen or additional weatherproofing multiple coats are recommended.

Coverage

Porous substrates 120-200 sq.ft. / gal /coat

Non-porous substrates 200-250 sq.ft. / gal /coat

Two coats are recommended for weatherproofing.

Technical Data

Flash point	>200 F Seta (non-flammable)
Density	8.5 lb/gal
Viscosity	approx 2000 cps
pH	9.0 - 9.8
Chemistry	100% acrylic
Solvent system	aqueous
Adhesion	Internal wet adhesion promoters

Features

- ◆ Meets VOC, VOS requirements
- ◆ Is easy to use; brush, roller or spray
- ◆ Does not create a vapor barrier
- ◆ Performs against all weather conditions
- ◆ Low odor and low toxicity
- ◆ Easy cleanup with water before drying
- ◆ Non-yellowing

Handling and Storage

Do not apply to frozen or saturated surfaces. Do not apply if precipitation is forecast within 8 hours of application. Do not apply if the temperature cannot be maintained above 40 F for 24 hours. Shelf life in closed containers is 18-24 months when stored at 50-100 F. Keep containers sealed and under cover when not in use.

Maintenance

If an area that has been coated with **T-WALL GLAZE 2000** becomes dirty or stained, clean with a mild cleaner solution and low-pressure spray rinse. For scars, broken or damaged areas, repairs should be made with the same products and then coated with **T-WALL GLAZE 2000**.

Precautions

T-WALL GLAZE 2000 is an alkaline water based material. Do not ingest. Avoid contact with skin and eyes. In case of contact, flush with water. For contact with eyes, get immediate medical attention in addition to flushing. Wear safety glasses and protective clothing. Keep out of reach of children and pets.