

Total Quality. Total Service. Total Satisfaction.

T-WALL Lastic Premier

Description

T-WALL Lastic Premier is our highest quality elastomeric coating. **T-WALL Lastic Premier** can be applied directly to concrete, concrete block, EIFS finishes, wood, asbestos shingles and other surfaces without the use of a primer.

T-WALL Lastic Premier provides a waterproof, attractive finish that has elasticity to bridge old and new cracks.

Application

Prepare surface by removing any dirt, oils, loose debris or any substance that may interfere with the bond. A dry surface is preferable but a slightly damp surface is acceptable. Glossy surfaces should be lightly sanded prior to application. It is advisable to fill any spalled or broken areas of substrate with a suitable patching material. Roll or brush over any cracks before coating the entire wall. Any cracks greater than: inch should be filled with a paintable grade acrylic caulk and allow to cure 4 hours before beginning coating.

Stir product for one minute with a low speed mixer or manually stick-stir as desired. Do not beat excessive air into the product. Apply **T-WALL Lastic Premier** by roller, brush or airless sprayer. For airless sprayer, use a reversible tip with a #35 orifice-spraying tip. For roller application, a 1.25-inch nap roller produces good results. The nap thickness can be varied to compensate for the substrate characteristics and the desired appearance. Thin product with up to 5 ounces of water per gallon if needed. For waterproofing, two 12-15 mil (wet) coats are recommended. When spray applying **T-WALL Lastic Premier**, it is suggested that the first coat is back-rolled to achieve the best results.

Coverage

Porous substrates 80-120 sq.ft. / gal /coat

Non-porous substrates 120-150sq.ft. / gal /coat

Two coats are necessary for waterproofing.

Features

- ◆ Has permanent elasticity to bridge cracks
- ◆ Meets VOC, VOS requirements
- ◆ Is easy to apply with water cleanup
- ◆ Does not create a vapor barrier
- ◆ Protects against all weather conditions
- ◆ Provides a long lasting, attractive finish
- ◆ Resists dirt pickup and is non-chalking

Technical Data

Flash point	>200 F	Seta
Density	11.8 lb/gal	
Viscosity	approx 25000 cps	
pH	9.0 - 9.5	
Elongation	500 %	ASTM D412
Actives	> 72%	ASTM D1044
Moisture Vapor Transmission	2.5 perms	ASTM E96
Pigment	non-chalking	UV rated

Handling and Storage

Do not apply to frozen or saturated surfaces. Do not apply if precipitation is forecast within 8 hours of application. Do not apply if the temperature cannot be maintained above 40 F for 24 hours. Shelf life in closed containers is 12-18 months when stored at 50-100 F. Cleanup with water or soapy water before drying.

Maintenance

If **T-WALL Lastic Premier** becomes dirty or stained, clean with a mild cleaner solution and low-pressure spray rinse. For scars or hard to clean stains, recoat with **T-WALL Lastic Premier**.

Precautions

T-WALL Lastic Premier is an alkaline water based material. Do not ingest. Avoid contact with skin and eyes. In case of contact, flush with water. For contact with eyes, get immediate medical attention in addition to flushing. Wear safety glasses and protective clothing. Keep out of reach of children and pets.