

*Total Quality. Total Service. Total Satisfaction.*

## Premium Fibered Stucco

**TOTAL WALL Premium Fibered Stucco** is a dry mix containing Portland cement, chopped strand fiber-glass reinforcement, microfibers for added strength and crack resistance, graded aggregates, and specialty modifiers designed to enhance workability and cure.

**TOTAL WALL Premium Fibered Stucco** does not require sand or other construction ingredients to be added. Only water is required to be added at the job site.

**TOTAL WALL Premium Fibered Stucco** may be used as the scratch coat and brown coat layers in a traditional hard coat stucco application. **TOTAL WALL Premium Fibered Stucco** may also be used as a one-coat hi-build stucco product.

### Directions

Add up to 4.75 quarts clean water per 50-pound Bag of **TOTAL WALL Premium Fibered Stucco**. Use low-speed mixing. After initial mixing, allow the mix to stand for 2-5 minutes, then re-mix, adding a small amount of water to adjust workability if necessary. Mix potlife will vary depending on temperature and batch size. An average potlife of 40 minutes can be anticipated. **TOTAL WALL Premium Fibered Stucco** may be retempered one time if mix becomes to stiff.

Options: **TOTAL WALL Liquid Acrylic Additive** may be used to replace 20% of the mix water. **TOTAL WALL Liquid Acrylic Additive** will improve the physical strength characteristics of the product and reduce the possibility of cracking. For an attractive and durable result, topcoat with any **TOTAL WALL Synthetic Finish**. **TOTAL WALL Synthetic Finishes** are available in several textures and unlimited colors.

### Technical Data

Chemistry - Portland cement based  
Aggregate - quartz and silica  
Modifiers - specialty cellulose and wetting agents  
Hydration Control - balanced lime blend  
Reinforcement - two types of fibers

### Limitations

Apply in accordance with standard lath and plastering practices. Do not apply to frozen walls or in temperatures below freezing. Use only clean potable mix water. Schedule work to avoid application in direct sun when possible. Moist curing of product is acceptable unless **TOTAL WALL Liquid Acrylic Additive** has been added.

### Warranty

There is no express or implied warranty of any type carried on this product.

### Availability

Net: 50-pound bags US dry weight

