

# INSULATED FIRE RATED ACCESS DOOR WITH DRYWALL BEAD

### Model KRP-350FR

For Walls And Ceilings

DATE



KARP ASSOCIATES. INC.

#### **SPECIFICATIONS**

#### **GENERAL SCOPE:**


The KRP-350FR is insulated and rated by Underwriters Laboratories for 1.5 hour "B" label in walls, and may be used in a 2 hour fire rated wall assembly. Additionaly, Warnock Hersey rated the KRP-350FR for 3 hours in ceilings.


#### CONSTRUCTION:

- 1. Frame shall be 16 gage steel, 1" wide, surrounded by galvanized drywall bead.
- 2. Door shall be 20 gage steel, welded pan type filled with 2" thick fire-rated insulation, and shall open to 175°, be self-latching with automatic closer and interior latch release.
- 3. Hinge shall be continuous piano hinge.
- 4. Latches shall be spring loaded sliding bolt type, keyed paddle latch, all keyed alike. Door can be prepared for a rim cylinder lock.
- 5. Finish shall be prime coat of rust inhibitive electrostatic powder, baked white enamel. Stainless steel doors shall have #4 satin finish.
- \* Fire rated insulation provides a noise reduction coeficent (NRC) of 1.0.


## STANDARD SIZES

DOOR SIZE	WALL/CEILING	NUMBER OF	SHIP WT.	
H X W (IN.)	OPENING (IN.)	LATCHES	(LBS.)	
8 x 8		1	6.1	
12 x 12	8 3/8 x 8 3/8	1	9.3	
14 x 14	12 3/8 x 12 3/8	1	12.2	
16 x 16	14 3/8 x 14 3/8	1	13.6	
18 x 18	16 3/8 x 16 3/8 18 3/8 x 18 3/8	1	18.2	
24 x 12	24 3/8 x 12 3/8	1	14.9	
22 x 22	22 3/8 x 22 3/8	1	23.5	
24 x 24	24 3/8 x 24 3/8	1	25.7	
30 x 22	30 3/8 x 22 3/8	1	26.8	
30 x 24	30 3/8 x 24 3/8	1	31.0	
30 x 30*	30 3/8 x 30 3/8	1	36.3	
32 x 32*	32 3/8 x 32 3/8	1	39.8	
36 x 22	36 3/8 x 22 3/8	2	33.1	
36 x 24	36 3/8 x 24 3/8 36 3/8 x 36 3/8	2	38.7	
36 x 36*	48 3/8 x 24 3/8	2	50.1	
48 x 24*	48 3/8 x 36 3/8	2	47.1	
48 x 36*	48 3/8 x 48 3/8	2	59.7	
48 x 48*		2	85.7	
*NOTE: All doors sized larger than 24" wide are for walls only.Not available for ceilings1"				





PROJECT SCHEDULE						
н	w	No. of Latches	Finish	Remarks		
	Н			N		





Made with Union Labor



FOR MORE INFORMATION CALL 1-888-926-1365